



Protect-All®

Flooring



1. Protect-All® Commercial Flooring Matte finish. Available in 5' x 8' and 5' x 5' sheets in dark gray, light gray, brown, terra cotta, black, burgundy, blue or green (applied smooth side up).
2. Protect-All 127 2-Part Epoxy Flooring Adhesive. Covers approximately 80 sf; is applied with a 1/8" V-notch trowel and has a working time of 15 – 30 minutes.
3. Protect-All 139 2-Part Epoxy Flooring Adhesive. Covers approximately 80 sf; is applied with a 1/8" V-notch trowel and has a working time of 10 – 25 minutes.
4. Protect-All Cove Base. Rolls are 1/4" x 6" x 30' available in dark gray, light gray, brown and black. Additional colors are cut by installer from 5' x 8' sheets at 80 lf. per sheet.
5. Aluminum or Stainless Steel Cove Cap/Z-Bar. Mechanically fastened every 12" to 18" on center.
6. & 6a. Eclectic 6100 Clear Sealant. Used around all drains, under the drain rings and transition strips, and additionally on top of the Cove Base. Each tube covers approximately 25 lf.
7. Protect-All Welding System. Available in dark grey, light grey, black, brown, terra cotta, and blue. Select from table below:

Protect-All Rapid Weld (available in all colors)
60 to 80 lf per cartridge for floor seams
80 to 100 lf per cartridge for base seams

8. Stainless Steel Trim Ring. Countersink to set flush with finished floor. Trim rings are required for ALL floor drains, floor sinks (round or square), trough drains, and clean outs.
9. Stainless Steel Corner Guard (2" x 2" x 4'). Recommended for ALL outside corners.
10. Stainless Steel Transition Strip (2 1/4" x 8'). Required for ALL transition and termination points.

*See the Protect-All Commercial Flooring Installation Manual for complete installation instructions.