



Protect-All Rapid Weld $^{\text{\tiny TM}}$  is a new installation system developed exclusively for Protect-All® flooring products. A faster and easier alternative to heat welding, Protect-All Rapid Weld is a chemical welding process available only to Protect-All distributors, dealers and installers.

## Features & Benefits

Faster installations - Protect-All Rapid Weld is a fast and easy system to teach and use. It increases productivity and reduces fatigue, compared to the traditional heat welding method.

Less downtime – Protect-All Rapid Weld dries fast, enabling quicker installations and less down-time.

Reduced labor – Protect-All Rapid Weld provides a competitive cost advantage by reducing installation time and the amount of required labor.

High quality – Protect-All Rapid Weld delivers consistent and enduring performance.



Dark Gray, Light Gray, Black, Terra Cotta, Blue, Green, and Brown, 490 ml cartridge sold individually or in 10-count boxes
Part A and Part B 10:1 mix ratio

**Usage rate:** Floor seams: 60 lf – 80 lf per cartridge

Base seams: 80 lf – 100 lf per cartridge

Cure time: Up to 30 minutes

**Shelf life:** One year from Manufacturer's Date

## Accessories

490 ml Protect-All Rapid Weld gun, manual
490 ml Protect-All Rapid Weld gun, cordless
2 Rechargeable Batteries
Battery Charger
Radius Finishing Tool
Floor Seam Finishing Tool
Rapid Mixing Nozzle
Seaming Tape
Groover Blade

## Physical Properties (Cured)

**Strength (PSI):** Shear 1,750 – 2,800

Tensile 2,500 - 3,500

Work time: 6 to 15 minutes

**Gap fill:** 3/16"

Temperature range: -40°F to 250°F





For more information, give us a call or visit our website today.

800-544-9538 protect-allflooring.com

Manufactured by Oscoda Plastics®, Inc.

5585 North Huron Avenue | Oscoda, Michigan 48750 | 989.739.6900 phone | 989.739.1494 fax | oscodaplastics.com







