

Rapid Weld™

For accelerated profits.



FAST FACTS

Protect-All Rapid Weld™ is a new installation system developed exclusively for Protect-All® flooring products. A faster and easier alternative to heat welding, Protect-All Rapid Weld is a chemical welding process available only to Protect-All distributors, dealers and installers.

Features & Benefits

Faster installations – Protect-All Rapid Weld is a fast and easy system to teach and use. It increases productivity and reduces fatigue, compared to the traditional heat welding method.

Less downtime – Protect-All Rapid Weld dries fast and enables installation and welding on the same day.

Reduced labor – Protect-All Rapid Weld provides a competitive cost advantage by reducing installation time and the amount of required labor.

High quality – Protect-All Rapid Weld delivers consistent and enduring performance.

Product Specifications

Dark Gray, Light Gray, Black, Terra Cotta, Blue, and Brown,
490 ml cartridge sold individually or in 10-count boxes
Part A and Part B 10:1 mix ratio

Usage rate: Floor seams: 60 lf – 80 lf per cartridge
Base seams: 80 lf – 100 lf per cartridge

Cure time: Up to 30 minutes

Shelf life: One year from Manufacturer's Date

Accessories

490 ml Rapid Weld gun, manual
490 ml Rapid Weld gun, cordless
2 Rechargeable Batteries
Battery Charger
Radius Finishing Tool
Floor Seam Finishing Tool
Rapid Mixing Nozzle
Seaming Tape
Groover Blade

Physical Properties (Cured)

Strength (PSI): Shear 1,750 – 2,800
Tensile 2,500 – 3,500

Work time: 6 to 15 minutes

Gap fill: 3/16"

Temperature range: -40°F to 250°F



For more information, give us a
call or visit our website today.

800-544-9538

protect-allflooring.com

Manufactured by Oscoda Plastics®, Inc.

5585 North Huron Avenue | Oscoda, Michigan 48750 | 989.739.6900 phone | 989.739.1494 fax | oscodaplastics.com

Oscoda Plastics and Protect-All are registered marks owned by Oscoda Plastics, Inc.
Protect-All Commercial Flooring is proudly manufactured in the United States of America.
PA Rapid Weld Fast Facts ORIG: 8.3.16 REV: 5.23.17 – OP080006

