

PROTECT-ALL® FLOORING WET AREA SYSTEM



1. Protect-All® Commercial Flooring Matte finish. Available in 5' x 8' and 5' x 5' sheets in dark gray, light gray, brown, terra cotta, black, burgundy, blue or green (applied smooth side up).
2. Protect-All 127 2-Part Epoxy Flooring Adhesive. Covers approximately 80 sf; is applied with a 1/8" V-notch trowel and has a working time of 15 – 30 minutes.
3. Protect-All 139 2-Part Epoxy Flooring Adhesive. Covers approximately 80 sf; is applied with a 1/8" V-notch trowel and has a working time of 10 – 25 minutes.
4. Protect-All Cove Base. Rolls are 1/4" x 6" x 30' available in dark gray only. Additional colors are cut by installer from 5' x 8' sheets at 80 lf. per sheet.
5. Aluminum or Stainless Steel Cove Cap/Z-Bar. Mechanically fastened every 12" to 18" on center.
6. & 6a. Eclectic 6100 Clear Sealant. Used around all drains, under the drain rings and transition strips, and additionally on top of the Cove Base. Each tube covers approximately 25 lf.
7. Protect-All Welding System. Select from tables below:

Protect-All Rapid Weld™ for all floor and base seams *Contact manufacturer for available colors*
Floor Seams 60 lf – 80 lf per 490 ml cartridge
Cove Base 80 lf – 100 lf per 490 ml cartridge

Protect-All Heat Weld (available in all colors)
V-Rod for Floor Seams – 450 lf per roll
Corner Rod for Cove Base – 450 lf per roll

8. Stainless Steel Trim Ring. Countersink to set flush with finished floor. Trim rings are required for ALL floor drains, floor sinks (round or square), trough drains, and clean outs.
9. Stainless Steel Corner Guard (2" x 2" x 4"). Recommended for ALL outside corners.
10. Stainless Steel Transition Strip (2 1/4" x 8'). Required for ALL transition and termination points.

*See the Protect-All Commercial Flooring Installation Manual for complete installation instructions.



Give us a call or visit our web site today.

800-544-9538

www.protect-allflooring.com

"Oscoda Plastics" and "Protect-All" are registered marks owned by Oscoda Plastics, Inc.
PA Wet Area System Sheet_V2_7.23.14 – M#OP14-0002