

COMMERCIAL APPLICATION CHECKLIST

1	Protect-All® Commercial Flooring Matte finish. Available in 5' x 8' and 5' x 5' sheets in dark gray, light gray, brown, terra cotta, black, burgundy, blue or green (applied smooth side up).
2	Protect-All 127 2-Part Epoxy Flooring Adhesive. Covers approximately 80 sf; is applied with a 1/8" V-notch trowel and has a working time of 15 – 30 minutes.
3	Protect-All 139 2-Part Epoxy Flooring Adhesive. Covers approximately 80 sf; is applied with a 1/8" V-notch trowel and has a working time of 10 – 25 minutes.
4	Protect-All Cove Base. Rolls are 1/4" x 6" x 30' available in dark gray only. Additional colors are cut by installer from 5' x 8' sheets at 80 lf. per sheet.
5	Aluminum or Stainless Steel Cove Cap/Z-Bar. Mechanically fastened every 12" to 18" on center.
6	Eclectic 6100 Clear Sealant. Used around all drains, under the drain rings and transition strips, and additionally on top of the Cove Base. Each tube covers approximately 25 lf.
7	Protect-All Welding System. Choose from below: 1. Protect-All Rapid Weld™ 2. Protect-All Heat Weld
8	Stainless Steel Trim Ring. Countersink to set flush with finished floor. Trim rings are required for <u>ALL</u> floor drains, floor sinks (round or square), trough drains, and clean outs.
9	Stainless Steel Corner Guard (2" x 2" x 4'). Recommended for <u>ALL</u> outside corners.
10	Stainless Steel Transition Strip (2 1/4" x 8'). Required for <u>ALL</u> transition and termination points.

Items listed above are specific to wet area applications; please see our installation manual for complete list & details of tools required for PROTECT-ALL installations.

800.544.9538
protect-allflooring.com

