

Technical Bulletin Bulletin 3: OP-003 Updated 6/2016

Welding Materials

Protect-All Rapid Weld

- Used for welding floor seams and cove base
- Specifications
 - o 490 ml cartridge
 - \circ 10:1 mix ration
 - Cure time is 6 to 10 minutes
 - 1 year shelf life from manufacturer's date
 - Ex: 215225
 - \circ 215=2015/225=day of the year 8/14
- Coverage rates
 - \circ Floor seams 60 80 lf
 - \circ Cove base 80 100 lf
- Accessories
 - Rapid Weld Kit
 - Cordless dispensing gun
 - 2 batteries
 - 1 charger
 - Floor seam finishing tool
 - Radius seam finishing tool
 - Rapid Weld tape
 - 180 lf per roll
 - Manual dispensing gun
 - \circ 490 ml mixing nozzles

NOTE: Rapid Weld cannot travel by air. It can only be shipped by ground transportation.

www.protect-allflooring.com



Technical Bulletin
Bulletin 3: OP-003
Updated 6/2016

1 - 11 Clu

- Used for welding floor sheets together
- Used with the following Protect-All colors; Blue, Burgundy, Green
- 450 lf per roll
- Use V-Weld tip
- Calibrate heat gun before each use to ensure proper seaming techniques
- Allow proper cooling before skiving the weld
- Weld short seams prior to welding wall-to-wall seams

Corner Rod

- Used for welding cove base to the floor sheets
- Used with following Protect-All colors; Blue, Burgundy, Green
- 450 lf per roll
- Calibrate heat gun before each use to ensure proper seaming techniques
- Skiving of the finished weld is not required

NOTE: V-Rod and Corner rod are not interchangeable

To learn more, contact the Technical Department at:

800.544.9538

www.protect-allflooring.com